

ELAN s.r.l. - Via Osimana, 70 - 60021 Camerano (AN) - Italy
Tel. +39.071.7304258 - Fax +39.071.7304282
Site Web: www.elan.an.it - E-mail: info@elan.an.it
R.E.A. AN n. 152242 - Cod. Fisc. e Part. IVA IT 01572590428



Camerano, March 2014

Certificate of Conformity

COAXIAL CABLES MINI HD

We, **ELAN s.r.l.**, **CERTIFY** that the cables marked with:

ELAN HD MINI 75 OHM LSZH - CEI 36762 C-4 (U₀=400V) – PA - <date of production + metres>

are manufactured in accordance with specifications below described.



MANUFACTURING TECHNICAL FEATURES

1. Center conductor:

The center conductor is made of bare copper - diameter 0.645 mm (22 AWG).

2. Insulation:

Insulation: Solid PE – nominal thickness 1.10 mm – diameter 2.90 mm.

3. Shield:

The shield is made of al/pol. foil and tinned copper braid
- construction 112x0.11 – coverage area >95% -

4. Jacket:

The jacket in purple **LSZH** compound (M1 type according CEI 20-11 standards) is fire retardant according to CEI 20-22/III Standards and with low smoke and zero halogen according CEI 20-37 (IEC 60754; IEC 61034; BSEN 50267; BSEN 50268) Standards.

Coax cables marked as C-4 (U₀=400V) owing to their technical characteristics and the positive results obtained by passing the tests and can be installed with electrical power cables marked both 450/750V, and 0,6/1 Kv according to CEI UNEL 36762 and can be used in outdoor applications.

Elan Srl



LOW SMOKE
EMISSION



HALOGEN FREE



ESTERNO /
OUTDOOR



FIRE RETARDANT



CON CAVI ELETT.
WITH POWER CABLES